



# SAFETY DATA SHEET

KODRIN WV 456

## 1. Identification of the preparation and of the company

- Product name and/or code** : KODRIN WV 456
- Manufacturer** : Akzo Nobel Decorative Coatings Ltd,  
PO Box 37,  
Hollins Road, Darwen, Lancashire,  
United Kingdom, BB3 0BG,  
Tel Number: +44 (0) 1254 704951  
Internet:
- e-mail address of person responsible for this SDS** : youngerd@akzonobel.commsdsinfo.uk@akzonobel.com
- Product use** : Waterborne coating for interior and exterior use.
- Emergency telephone number of the company** : +44 1254 704951 (24 Hours/day, every day)
- International Sikkens emergency number : +31 71 3086944  
available 24 hours/day, every day of the week

## 2. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS number	%	EC number	Classification
propylene glycol	57-55-6	2.5 - 10	200-338-0	Not classified.
ethanol, 2-(2-ethoxyethoxy)-	111-90-0	1 - 2.5	203-919-7	Xi; R36
xylene	1330-20-7	1 - 2.5	215-535-7	R10 Xn; R20/21 Xi; R38
See section 16 for the full text of the R-phrases declared above				

Workplace exposure limits, if available, are listed in section 8.

## 3. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

- Classification** : Not classified.
- Additional warning phrases** : Safety data sheet available for professional user on request.

## 4. First-aid measures

### First-aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

## 5. Fire-fighting measures

- Extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

## 6. Accidental release measures

- Personal precautions** : Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product enters drains or sewers, immediately contact the local water company; in the case of contamination of streams, rivers or lakes, the relevant environment agency.

**Note:** see section 8 for personal protective equipment and section 13 for waste disposal.

## 7. Handling and storage

- Handling** : Keep container tightly closed.
- Avoid contact with skin and eyes. Avoid inhalation of vapour, spray or mist.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator

## 7. Handling and storage

during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

The Manual Handling Operations Regulations may apply to the handling of containers of this product. Packs with a volume content of 5 litres or more may be marked with a maximum gross weight.

To assist employers the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight

### Storage

- : Store in accordance with local regulations. Must be stored in a dry location. Keep container in a well-ventilated place. Keep away from: oxidising agents, strong alkalis, strong acids.
- No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
- Do not empty into drains.

## 8. Exposure controls/personal protection

### Engineering measures

- : All engineering control measures used to control exposure to hazardous substances must be selected, maintained, examined and tested to meet the requirements of the Control of Substances Hazardous to Health Regulations (COSHH). Similarly all personal protective equipment, including respiratory protective equipment, must be selected, issued and maintained to meet the requirements of COSHH. These requirements include the provision of any necessary information, instruction and training with regard to their use. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.

<u>Ingredient name</u>	<u>Workplace exposure limits</u>
propylene glycol	<b>EH40-WEL (United Kingdom (UK), 9/2006).</b> WEL 8 hrs limit: 10 mg/m <sup>3</sup> 8 hour(s). WEL 8 hrs limit: 150 ppm 8 hour(s).
xylene	<b>EH40-WEL (United Kingdom (UK), 9/2006). Skin</b> WEL 15 min limit: 441 mg/m <sup>3</sup> 15 minute(s). WEL 15 min limit: 100 ppm 15 minute(s). WEL 8 hrs limit: 220 mg/m <sup>3</sup> 8 hour(s). WEL 8 hrs limit: 50 ppm 8 hour(s).

### Personal protective equipment

#### Hands

##### Gloves

- : For prolonged or repeated handling, use the following type of gloves:

Recommended: foil, fluor rubber

Not recommended: nitrile rubber, neoprene, butyl rubber, PVC

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

## 8. Exposure controls/personal protection

**Eyes** : Use safety eyewear designed to protect against splash of liquids.

### Environmental exposure controls

Do not allow to enter drains or watercourses.

## 9. Physical and chemical properties

**Physical state** : Liquid.  
**Flash point** : Not applicable.  
**Viscosity** : Kinematic: 2,44 cm<sup>2</sup>/s (244 cSt)  
**Relative density** : 1,025  
**Solubility** : Easily soluble in the following materials: cold water.

## 10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

## 11. Toxicological information

There is no data available on the preparation itself. The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethanol, 2-(2-ethoxyethoxy)-	LD50 Dermal	Rat	6 mL/kg	-
	LD50 Dermal	Rabbit	4200 uL/kg	-
	LD50	Rat	360 ug/kg	-
	Intraperitoneal			
	LD50	Rat	4 g/kg	-
	Intravenous			
	LD50 Oral	Rat	7500 mg/kg	-
	LD50 Oral	Rat	5500 uL/kg	-
	LD50	Rat	6 g/kg	-
	Subcutaneous			
xylene	LD50 Unreported	Rat	7500 mg/kg	-
	LD50 Dermal	Rabbit	>1700 mg/kg	-
	LD50	Rat	2459 mg/kg	-
	Intraperitoneal			
	LD50 Oral	Rat	4300 mg/kg	-
	LD50	Rat	1700 mg/kg	-
	Subcutaneous			

**Conclusion/Summary** : Not available.

### Chronic toxicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

## 11. Toxicological information

### Mutagenicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

## 12. Ecological information

There is no data available on the preparation itself.  
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
ethanol, 2-(2-ethoxyethoxy)-	Mortality	Acute LC50 26500 mg/L	Fish	96 hours
	Mortality	Acute LC50 21400 mg/L	Fish	96 hours
	Mortality	Acute LC50 13900 mg/L	Fish	96 hours
	Mortality	Acute LC50 13400 mg/L	Fish	96 hours
	Mortality	Acute LC50 >10000 mg/L	Fish	96 hours
	Mortality	Acute LC50 9650 mg/L	Fish	96 hours
xylene	Mortality	Acute LC50 13,4 mg/L	Fish	96 hours
	Mortality	Acute LC50 13,3 mg/L	Fish	96 hours
	Mortality	Acute LC50 12 mg/L	Fish	96 hours
	Mortality	Acute LC50 8,6 mg/L	Fish	96 hours
	Mortality	Acute LC50 8,2 mg/L	Fish	96 hours
	Mortality	Acute LC50 3,3 mg/L	Fish	96 hours

**Conclusion/Summary** : Not available.

### Biodegradability

**Conclusion/Summary** : Not available.

## 13. Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

## 14. Transport information

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### Sea

**Special provisions** : Not available.

**Marine pollutant** : No.

### Air

**Special provisions** : Not available.

The "viscosity exemption" provisions do not apply to air transport.

**This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.**

## 15. Regulatory information

**EU regulations** : The product is determined as not being dangerous according to the requirements of the DPD.

**Risk phrases** : This product is not classified according to EU legislation.  
S2- Keep out of the reach of children.  
S46- If swallowed, seek medical advice immediately and show this container or label.

**Additional warning phrases** : Safety data sheet available for professional user on request.

## 16. Other information

**CEPE Classification** : 7

**Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)** : R10- Flammable.  
R20/21- Harmful by inhalation and in contact with skin.  
R36- Irritating to eyes.  
R38- Irritating to skin.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

The information contained in this safety data sheet is provided in accordance with the requirements of the CHIP Regulations.

Further information and relevant advice can be found in:

- The Control of Substances Hazardous to Health Regulations (As amended).
- The Manual Handling Operations Regulations (As amended).
- The Environmental Protection (Duty of Care) Regulations (As amended).
- 'EH40 : Workplace exposure limits.

**Date of issue** : 1-10-2007.

**Version** : 5

**Notice to reader**

## 16. Other information

**FOR PROFESSIONAL USE ONLY**

**IMPORTANT NOTE** *The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.*

*Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.*

**Head Office**

**Akzo Nobel Decorative Coatings B.V, Rijksweg 31, 2171 AJ Sassenheim, the Netherlands**